



TPK-40-xxx/3+0/(S) Power supply system: TNC

Power Surge Protector | Type 2 / Class II

Plug-in format


TPK-40-xxx is the range of devices for discharging induced transient overvoltages (Type 2 / Class II), in accordance with EN/IEC 61643-11. DIN rail plug-in format. Ability to discharge induced voltage surges (8/20 μ s).

- Suitable for the second stage of protection in supply distribution panels in which Type 1 protection devices are installed, or for the first stage of protection in residential, commercial or other applications not exposed to direct strikes and with no external lightning protection system.
- Discharge capacity with an 8/20 μ s waveform. Imax: 40 kA.
- Exclusive devices for TNC earthing systems.
- Exclusive devices which are compatible with Power Line Communication networks.
- Biconnect - two types of terminal: for rigid or flexible cable and for fork type comb busbar.
- Available with optional remote signalling

Application AC/DC distribution
Power supplies
Industrial automation
Telecommunications
Motor controls systems
PLC applications
Power transfer equipment
HVAC applications
AC drives
UPS systems
Security systems
IT / Data centers
Medical equipment

Features/Benefits


- Easy installation or retrofit
- Din-rail mountable
- Fail-safe /self-protected design
- Remote indicator (optional) with 3 pin NO/NC contact
- IP20 finger-safe design
- Visual indicator
- Small foot print



Data sheet

Type	TPK-40-xxx/3+0/(S)
Technical Data	
Power supply system	TNC
Maximum continuous voltage (Uc)	275 / 320 / 385 / 420V
SPD to EN 61643-11	Type 2
SPD to IEC 61643-11	class II
Nominal discharge current (8/20 μ s) (In)	20kA
Maximum discharge current (8/20 μ s) (Imax)	40kA
Voltage protection level (Up)	≤ 1.3 / 1.5 / 1.8 / 2.0kV
Response time (tA)	< 25ns
Thermal Protection	YES
Operating State/Fault Indication	Green (good) / Red (replace)
Degree of protection	IP 20
Insulating material / flammability class	PA66,UL94 V-0
Temperature range	-40° C~+80° C
Altitude	13123 ft [4000m]
Conductor Cross Section (max)	35mm ² (Solid) / 25mm ² (Flexible)
Format	Pluggable
For mounting on	DIN rail 35mm
Place of installation	indoor installation
Remote Contacts (RC)	Optional
Type of remote signalling contact	changeover contact
Cross-sectional area for remote signalling terminals	max. 1.5 mm ² solid / flexible

Dimensions



Internal configuration

