



TPKW-F/75C-FF

Data and Signal Surge Protection

SPD for Coaxial & Radio frequency (RF) Systems

TPKW is the series of devices for discharging transient overvoltages induced in coaxial lines. In accordance with IEC 61643-21. Coaxial format.

- Suitable for the protection of radiofrequency transmission and reception equipment. By their nature, they are highly exposed to induced transient overvoltages (surges) associated with meteorological activity.
- For F connectors.
- Ideal for the protection of transmission and reception systems such as TV and radio antennas, closed circuit TV (CCTV), alarms, etc.
- Discharge capacity with an 8/20 μ s waveform: 20 kA.

Application

- TV and Settop Tuners
- Antenna
- Cable TV
- Broadband
- Networks
- Security Systems

Features/Benefits

- Easy installation
- Low Insertion Loss
- Wide operating frequency spectrum
- Very fast response
- High Energy GDT Technology
- Field Replaceable GDT
- Waterproof Design
- DC Pass configuration
- Bi-Directional Protection
- Good transmission effect
- Strong anti-interference
- complies IEC 61643-21 standard

Data sheet

Type	TPKW-F/75C-FF
Technical Data	
Frequency	0-3GHZ
Maximum continuous operating voltage (Uc)	75V
Nominal discharge current (8/20 μ s) (In)	10kA
Maximum discharge current (8/20 μ s) (Imax)	20kA
Voltage protection level (8/20 μ s) (Up)	\leq 600V
Maximum Current	10A
Maximum peak power	200W
Impedance	75 Ω
Insertion Loss	< 0.2dB
Return Loss	> 20dB
VSWR	< 1.2:1
Response time (tA)	< 100ns
Degree of protection	IP 67
Enclosure Material	Metal
Temperature range	-40° C~+80° C
Altitude	13123 ft [4000m]
Connection	F (Female, Female)
Housing	In-line Installation
Field Replaceable GDT	YES
Type of SPD	C2,C3
Product standards	IEC 61643-21

Dimensions

